

SchwankAir

USA

Schwank USA Inc.

2 Schwank Way
Waynesboro, GA 30830
Tel.: 1-887-446-3727

E-mail: csr@schwankgroup.com
Website: www.schwankair.com

CANADA

Schwank Ltd.

5285 Bradco Blvd.
Mississauga, ON, L4W 2A6
Tel.: 1-887-446-3727

E-mail: csr@schwankgroup.com
Website: www.schwankair.com

1000 Series Air Curtain Specifications

Features: Brushed aluminum front panel. Top intake, with decorative side panels. Full length articulating discharge nozzle. Two speed output.

Mounting Options included: Full length steel rear mounting bracket. Painted steel side wall mounting brackets.

Operating options included: Automatic activation using magnetic reed switch. Remote control. On/Off Hi/Low buttons on unit.

Installation height: Up to 7' [213cm]

Electrical: 115 Volt, 1 Phase, 60Hz. Factory wired 7.5' [228cm] grounded power cord.

Motors: 120 Volt, 1 Phase, 60Hz. 1/5 HP, 2 speed, TEAO, direct drive, internally protected, auto reset.

Certification: CSA & UL

Model	Motor	Fans: 4 ¾" [120mm] Forward curve	FLA	CFM	FPM	Ave dB rating @ 10' [305cm]	Weight
1003	1 @ 30W, 1 @ 60W	3	2.7	647 high / 530 low	3150 high / 2500 low	52 high / 49 low	35 lbs. / 16 kg
1004	2 @ 60W	4	3.5	883 high / 706 low	3150 high / 2500 low	52 high / 49 low	40 lbs. / 18 kg
1006	3 @ 60W	6	5.25	1340 high / 1060 low	3150 high / 2500 low	52 high / 49 low	57 lbs. / 26 kg